

Tag: 248R	Device ID 1990266	PV: Snsr1	Rosemount	248
	MVar Primary Cfg	Uses DOF 263B0201	57 Variables	8/4/06 11:06 AM
Tag:	248R			
Date:	38894			
Descriptor:	CHANGE			
Message:	MMMM			
Manufacturer:	Rosemount			
Model:	248 Temp			
Dev id:	1990266			
Distributor:	Rosemount			
Universal rev:	5			
Fld dev rev:	2			
Software rev:	1			
Hardware rev:	4			
Snsr 1 Type:	T/C typ K			
Snsr 1 Conn:	2 Wire			
Snsr S/N:	0			
Snsr damp:	2 S			
2 Wire Offset:	0 ohms			
Snsr1 LSL:	-180 degC			
Snsr1 USL:	1372 degC			
Lor-Min trim lim:	-180 degC			
Lor-Max trim lim:	1372 degC			
Upr-Min trim lim:	-180 degC			
Upr-Max trim lim:	1372 degC			
Snsr 1 Lor trim pt:	-79.948 degC			
Snsr 1 Upr trim pt:	105.987 degC			
Termnl Units:	degC			
Termnl Damp:	0 S			
Termnl LSL:	-60 degC			
Termnl USL:	100.004 degC			
PV is:	Snsr1			
SV is:	Termnl			
Snsr damp:	2 S			
Snsr 1 Units:	degC			
Snsr Lor Rng:	-50 degC			
Snsr Upr Rng:	150 degC			
Snsr1 LSL:	-180 degC			
Snsr1 USL:	1372 degC			
Snsr Min Span:	0.01 degC			
Xfer Fcn:	Linear			
AO alrm type:	Hi			
Low Alarm:	3.75 mA			
High Alm:	21.75 mA			
Low Sat.:	3.9 mA			
High Sat.:	20.5 mA			
Poll addr:	0			
Num req preams:	6			
Physicl signl code:	Bell 202 current			
Write protect:	No			
Final asmbly num:	171564			
Max Snsrs:	1			
50/60 Hz filter:	60 Hz			
Active Calibrator:	Off (Normal)			
Open Snsr Holdoff:	Normal			

Intermit Detect:	On (Normal)			
Intermit Thresh:	0.2	%		
Burst mode:	Off			
Burst option:	PV			
numdu:	Bad36			
Snsr1 LSL:	0	degC		
Snsr1 USL:	0	degC		
Snsr Min Span:	0.01	degC		
Termnl Units:	degC			
Termnl LSL:	-60	degC		
Termnl USL:	100.004	degC		
Termnl min span:	0.01	degC		