

A trusted leader in measurement & calibration solutions.

meriam.com 1 (800) 817-7849



# 10 Pressure Gauges in 1 Device -\$1200.00 -\$1200.00 -\$1200.00 \$3150.00 \$3600.00

# meriGauge® plus

#### The meriGauge® plus Digital Pressure Gauge is

the perfect solution for multi-range pressure measurement needs.

As the only modular gauge on the market, the meriGauge plus delivers significant cost savings by allowing

Intrinsically Safe

users to purchase a single gauge and add only the pressure ranges they need. With 22 interchangeable Smart Sensors available (15 psi – 3,000 psi), the meriGauge plus is actually multiple gauges in one device, creating the flexibility and lowest cost of ownership only Meriam can provide.

#### **Easy to Use**

- Icon based, simple buttons
- Gauge works with all meriSense sensors
- Portable or fixed installation, even in narrow spaces

#### **Easy to Read**

- Concisely displays more info at a glance
- High visibility from a distance
- Crisp digital readout in any or no light

## meriSense™

#### **Smart Sensor Modules**

- 10 Interchangeable Smart Sensor Modules
- Compound Gage Pressure Range -14.5 to 3000 PSIG
- · Absolute Pressure Range 0 to 100 PSIA
- Isolated Sensors for fluids compatible with 316SS
- NIST Traceable Calibration
- Hot Swappable



A trusted leader in measurement & calibration solutions.

meriam.com 1 (800) 817-7849

## meriGauge® plus

### meriSense

**Smart Sensor Modules** 

Display	6-digit main height, 17.8 mm (0.701 in) 10-character height, 7.65 mm (0.301 in) White LED backlight (3 intensities and O) Red (beacon) error backlight	Body	Stainless Steel, 25.1 mm $\times$ 82.8 mm $\times$ 22.2 mm (0.989 in $\times$ 3.26 in $\times$ 0.875 in) Approx. weight 0.1 kg (0.22 lbs)
Keyboard	5-dedicated keys, plus information key Intuitive, icon-based keys for internationalization	Pressure Sensor  Accuracy	316SS Isolated Compound Isolated, –14.5 psi to FS, where FS is 15 psi to 3 000 psi Absolute Isolated, 0 psi to FS, where FS is 15 psi to 100 psi  Compound
Body	Powder coated T6 aluminum, 120.7 mm $\times$ 167.3 mm $\times$ 40.1 mm (4.75 in $\times$ 6.59 in $\times$ 1.58 in) body only Approx. weight with batteries 0.608 kg (1.34 lbs)		
meriSense Receptacle	Easy insertion/removal without tools Impossible to insert meriSense incorrectly Industrial stainless- steel release pin O-rings for alignment and vibration isolation Gold connection pins good for >1M cycles	,	0 to 110 % of Range: ± (0.02 % of Full Scale) + 0 to 110 % of Range: (0.005 % of Reading) Vacuum*: ± (0.02 % of Full Scale) *Vacuum = -14.5 psi  Absolute 0 to 110 % of Range: ± (0.02 % of Full Scale) +
Power and Battery Life	4 x 1.5 V AA alkaline Approx. 350+ hours with alkaline (no backlight)	v .	0 to 110 % of Range: (0.005 % of Reading)
Communication	USB mini 2.0 compliant, for conguration, update, user calibration and data log	Vent	1 mm Gortex, shielded when installed in meriGauge plus (cap provided)
	•	Process Connection	1/4 inch NPT
Storage	Data Log Pro*** provides a maximum 128 files or 100,000 data points Real-time clock calendar w/7 year battery backup	Electrical Connections	Hardened gold (30 micron) connection good for >1M cycles
Features	Modes: Min, Max, Accuracy, Tare, Average, Rate of change, DataLog Lite**, Ambient temperature/time Fully congurable via meriLink* PC Software Update rate, 5 measurements per second	Features	32 engineering units, two custom units, User calibration, fully congurable via meriLink PC Software
Operating Conditions	Conditions: −10 °C to 50 °C (14 °F to 122 °F)	Operating Conditions	Conditions: –10 °C to 50 °C (14 °F to 122 °F)
Shock Condition	Tested to survive a 39.4 inch [1 m] drop onto concrete	Shock Condition	Tested to survive a 39.4 inch [1 m] drop onto concrete
Ingress Protection	IP66	Ingress Protection	IP67
Intrinsically Safe	<b>C €</b> 0539	Intrinsically Safe	<b>C €</b> 0539
Environmental Protection	RoHS, WEEE	Environmental Protection	RoHS, WEEE
EMC Compatibility	For Handheld Class A device	EMC Compatibility	For Handheld Class A device

<sup>\*</sup> meriLink configuration software is included with each meriGauge plus.

<sup>\*\*</sup> Data Log Lite is included with every meriGauge plus.

<sup>\*\*\*</sup> Data Log Pro is an option you may purchase.