

Ordering Information

When ordering Meriam's orifice flanges, simply choose to the part number on these pages that fits your application. Flange rating options are available in 300#. Connection options include slip-on, weld neck or threaded.


Model 952 FS 30 - forged steel, slip-on welding; 300 lb. raised face

For systems where welded connections are required. These flanges are slipped over the pipe which is brought flush with the flange face. The pipe is then welded to the flange.

Model 952

Orifice Flanges

Meriam raised face orifice flange unions are designed to provide a convenient, accurate method for installing orifice plates. They incorporate accurately positioned pressure taps for connecting the flow measuring instruments. This eliminates the requirement of locating pressure taps in the field. Improper location of these taps will result in poor accuracy of the flow measuring system. These built-in taps also reduce field installation labor necessary for welding, drilling and/or tapping pressure taps on the flow line itself. Meriam orifice flanges are provided complete with nuts, bolts, gaskets and plugs for installation with no other parts required.



Line Pipe Size	Flange O.D. A	Bore Dia. B	Hub Length C	Dia. Raised Face	No. of Holes	Dia. of Holes	Dia. of Bolts	Length of Bolts	Bolt Circle D	Approx. Union Weight
1	47/8	13/8	17/8	213/16	4	11/16	5/8	4	31/2	15 lbs.
11/4	5¼	1 ²³ / ₃₂	1 13/16	33/16	4	11/16	5/8	4	37/8	17 lbs.
11/2	61//8	131/32	17/8	311/16	4	13/16	3/4	41/4	41/2	19 lbs.
2	6½	27/16	1 15/16	4 ⁵ / ₁₆	8	11/16	5/8	4	5	23 lbs.
21/2	7½	215/16	2	51/16	8	¹³ / ₁₆	3/4	41/4	57/8	31 lbs.
3	81/4	39/16	21/16	513/16	8	¹³ /16	3/4	41/4	6 ⁵⁄8	39 lbs.
4	10	49/16	21//8	71/16	8	13/16	3/4	41/4	7 ½	60 lbs.
5	11	5 ²¹ / ₃₂	21//8	83/8	8	7/8	3/4	41/4	91/4	70 lbs.
6	12½	6 ²³ / ₃₂	21//8	9¾	12	7/8	3/4	41/4	105/8	100 lbs.
8	15	8 ²³ / ₃₂	27/16	12	12	1	7/8	41/2	13	134 lbs.
10	171/2	107/8	25/8	141/8	16	11/8	1	51/4	15¼	196 lbs.
12	201/2	12 ⁷ /8	27/8	16½	16	11/4	11//8	5½	17¾	281 lbs.
14	23	143/16	3	19	20	11/4	11/8	5¾	201/4	380 lbs.
16	25½	163/16	31/4	211//8	20	13/8	11/4	61/4	221/2	620 lbs.
18	28	183/16	3½	233/8	24	13/8	11/4	61/2	24¾	691 lbs.
20	30½	203/16	3¾	255/8	24	13/8	11/4	6¾	27	781 lbs.
24	36	24 ³ / ₁₆	4 ³ / ₁₆	303/8	24	1 5/8	1½	71/2	32	1201 lbs.

All Dimensions are in inches


Model 952



Orifice Flanges

Model 952 FW 30 - forged steel, welding neck; 300 lb. raised face

Similar to slip-on welding model but for use where weld neck is preferred. These flanges are butted up against the ends of the pipe and welded in place.




						Drilling Template					
	Line Pipe Size	Flange O.D. A	Bore Dia. B	Hub Length C	Dia. Raised Face	No. of Holes	Dia. of Holes	Dia. of Bolts	Length of Bolts	Bolt Circle D	Approx. Union Weight
	1	47/8	13/8	17//8	213/16	4	11/16	5/8	4	31/2	15 lbs.
	11⁄4	51/4	1 ²³ / ₃₂	113/16	3 ³ /16	4	11/16	5/8	4	37/8	17 lbs.
	1½	61//8	1 ³¹ /32	17/8	3 ¹¹ /16	4	¹³ / ₁₆	3/4	41⁄4	41/2	19 lbs.
	2	61/2	2 ⁷ /16	1 ¹⁵ /16	4 ⁵ / ₁₆	8	11/16	5/8	4	5	23 lbs.
	21/2	71/2	215/16	2	51/16	8	¹³ / ₁₆	3/4	41⁄4	57/8	31 lbs.
	3	81⁄4	39/16	21/16	5 ¹³ / ₁₆	8	13/16	3/4	41⁄4	65/8	39 lbs.
	4	10	4 ⁹ / ₁₆	21/8	71/16	8	13/16	3/4	41/4	7 ⁷ /8	60 lbs.
	5	11	5 ²¹ / ₃₂	21/8	83/8	8	7/8	3/4	41/4	91/4	70 lbs.
	6	12½	6 ²³ /32	21/8	9¾	12	7/8	3/4	41/4	105/8	100 lbs.
	8	15	8 ²³ / ₃₂	27/16	12	12	1	7/8	41/2	13	134 lbs.
	10	171/2	107/8	25/8	141//8	16	11/8	1	51⁄4	151/4	196 lbs.
	12	20½	127/8	27/8	16½	16	11⁄4	11//8	5½	17¾	281 lbs.
NS	14	23	14 ³ / ₁₆	3	19	20	11⁄4	11//8	5¾	201/4	380 lbs.
	16	25½	16 ³ /16	31/4	211//8	20	13/8	11⁄4	61⁄4	22½	620 lbs.
	18	28	18 ³ / ₁₆	31/2	233//8	24	13/8	11⁄4	61/2	24¾	691 lbs.
	20	30½	203/16	3¾	255/8	24	13/8	11⁄4	6¾	27	781 lbs.
	24	36	243/16	43/16	303/8	24	15/8	1½	71/2	32	1201 lbs.

Drilling Template

Model 952 FT 30 - forged steel, threaded; 300 lb. raised fa

Designed for systems where threaded connections are suitable and conditions require forged steel.



Line Pipe Size	Flange O.D. A	Hub Length B	Dia. Raised Face	No. of Holes	Dia. of Holes	Dia. of Bolts	Length of Bolts	Bolt Circle C	Approx. Union Weight
1	47/8	17/8	2 ¹³ /16	4	11/16	5/8	4	3½	15 lbs.
11⁄4	51/4	1 ¹³ /16	33/16	4	11/16	5/8	4	37/8	17 lbs.
11/2	61//8	17/8	3 ¹¹ / ₁₆	4	¹³ / ₁₆	3/4	41⁄4	41/2	19 lbs.
2	6½	115/16	45/16	8	11/16	5/8	4	5	23 lbs.
21/2	71/2	2	51/16	8	13/16	3/4	41⁄4	57/8	31 lbs.
3	81/4	21/16	513/16	8	13/16	3/4	41⁄4	65/8	39 lbs.
4	10	21/8	71/16	8	13/16	3/4	41⁄4	77/8	60 lbs.
5	11	21//8	83/8	8	7/8	3/4	41⁄4	91⁄4	70 lbs.
6	121/2	21/8	9¾	12	7/8	3/4	41⁄4	105/8	100 lbs.
8	15	27/16	12	12	1	7/8	41/2	13	134 lbs.
10	17½	25/8	141/8	16	11//8	1	51⁄4	151⁄4	196 lbs.
12	20½	27/8	16½	16	11⁄4	11//8	51/2	17¾	281 lbs.

All Dimensions are in inches

Drilling Template